

# *PowerStak*

*Powered Walkie Stackers*



**Presto** LIFTS

# The PowerStak™ Difference

Presto PowerStak™ is a family of high performance, fully powered stackers that offer significant performance advantages over manual stackers without a significant price premium.

PowerStak Stackers provide instant flexibility and versatility. Whether used as a dedicated stacker, or as a combination stacker/work positioner, or as a transporter, they provide significant improvements in worker productivity. An abundance of ergonomic features make PowerStak Stackers the safest, easiest to operate

powered stackers available. Sleek, stylish design, low overall weight, and quiet operation allow them to fit nicely into a wide variety of work environments including: **warehouses, loading docks, light assembly work cells, retail sales floors and more.**

Seven PowerStak models are available to satisfy any requirement including servicing racks up to 12 feet high. Fork Over models can be used with open bottom pallets or skids and adjustable straddle units are available for use with any pallet style, even closed bottom.

PowerStak  
Narrow Mast  
2,200 lb. Capacity



PowerStak  
Extended Mast  
2,200 lb. Capacity




PowerStak Heavy-Duty  
Extended Mast  
3,000 lb. Capacity




Narrow mast and offset design provide workers a clear view with no blind spots.



Adjustable fork carriage allows forks to be repositioned to best accommodate loads (straddle only).




Auto-reversing "belly bump" switch protects against operator accidents while working in tight quarters.



Ergonomic handle with comfort-grip controls and switch redundancy for left- or right-hand operation.




Tight turning radius allows PowerStak to work in much narrower aisles than conventional forklift trucks.



Turtle speed setting reduces drive speed by 50% for precise positioning or when working in tight quarters



Sealed, maintenance-free AGM batteries and heavy-duty built in charger with fuse protection.




Solid steel straddle legs provide rigidity and eliminate deflection even under maximum load conditions.

## Straddle Design



Model	PPS2200-62NAS	PPS2200-101AS	PPS2200-125AS	PPS2200-150AS	PPS3000-125AS
Lift Height	62"	101"	125"	150"	125"
Capacity	2,200 lbs.	2,200 lbs.	2,200 lbs.	2,200 lbs.	3000 lbs.
Load Center	24"	24"	24"	24"	24"
Forks (adjustable welded)	42"	42"	42"	42"	42"
Individual Fork Width	6"	6"	6"	6"	4" forged
Straddle I.D. (adjustable)	40" – 50"	40" – 50"	40" – 50"	40" – 50"	40.125" – 50"
Max. Overall Width (straddle legs)	48" – 58"	48" – 58"	48" – 58"	48" – 58"	48" - 58"
Overall Height (lowered/raised)	80" / 80"	73" / 122.5"	85" / 146.5"	99" / 172.75"	86" / 150"
Weight (without load)	1,050 lbs.	1,390 lbs.	1,445 lbs.	1,610 lbs.	2500 lbs.
Lifting Speed (without load)	4.8" / sec.	4.8" / sec.	4.8" / sec.	4.8" / sec.	5" / sec.
Turning Radius	54"	58"	58"	58"	67"
Drive Motor	750 Watt	750 Watt	750 Watt	750 Watt	1.5 KW
Battery (2)	12 volt 75 amp hr	12 volt 75 amp hr	12 volt 75 amp hr	12 volt 75 amp hr	12 volt 150 amp hr

Adjustable width  
Straddle Legs on all units



## Fork Over Design



Model	PPS2200-62NFO-21	PPS2200-62NFO-27
Lift Height	62"	62"
Capacity	2,200 lbs.	2,200 lbs.
Load Center	24"	24"
Fork Length	42"	42"
Individual Fork Width	6"	6"
Max. Distance Between Forks	9"	15"
Max. Overall Width of Forks	21"	27"
Overall Height	78"	78"
Overall Width	32"	32"
Weight (without load)	900 lbs.	900 lbs.
Lifting Speed (without load)	4.8" / sec.	4.8" / sec.
Turning Radius	53"	53"
Drive Motor	750 Watt	750 Watt
Battery (2)	12 volt 75 amp hr	12 volt 75 amp hr



## Options

PowerStak units are available with these standard options. Other options may be available. Not all options shown are available for every PowerStak Model. Consult factory for details.

**Load Backrests** - to prevent loads from shifting when raised to full height

**Rubber Drive Wheel** - for better traction on uneven surfaces


**Non-Marking Rubber Drive Wheel** - to prevent scuffing/marking of floors

**Forged Forks** - one piece construction for maximum strength and rigidity

# PowerStak Counterbalance Stackers

Presto Counterbalance Stackers are ideal for die handling or machine feeding applications where straddle legs could get in the way. They can also be used for servicing rack or loading and unloading trucks. Unit comes standard with manual adjustable tilt mast.

<b>Model</b>	<b>PPS1100-62-CB</b>
Lift Height	62"
Capacity	1,100 lbs.
Load Center	15"
Fork Length	30"
Individual Fork Width	3"
Overall Height	82"
Overall Width	32"
Lifting Speed (without load)	3.2" / sec.
Weight (without load)	1,499 lbs.
Battery (2)	12 volt 100 amp hr



Works with any style pallet or skid, even closed bottom.



## Other Presto Stackers



**Lift Stik™**



**Counterweight Stackers**



**Manual Stackers**



**Pallet Stackers**



**Straddle Stackers**



**Specialty Stackers**

## The PowerStak Warranty

Presto Lifts warrants the Power Stacker against defects on the mast, fork carriage, chains, pumps, DC motors, controllers, cylinders and wiring harnesses from faulty material and workmanship for a period of one (1) year from the date of invoice.

All wear items such as batteries, wheels, motor brushes, seals, bearings, hydraulic hoses, all switches, battery chargers and forks have a limited warranty against defects in faulty material and workmanship for a ninety (90) day period from the date of invoice and 30 day limited warranty on labor. Please note that prior authorization from Presto Lifts is required on all warranty work.



Dealer Imprint

Presto Lifts Inc. • 50 Commerce Way • Norton, MA 02766  
 1.800.343.9322 • www.PrestoLifts.com • info@PrestoLifts.com

**Presto** LIFTS